

出来形管理図表 (アスファルト舗装工)

検測者 ワイズ 太郎

() は規格値
[] は社内規格値

検測年月日	測点	基準高EL1 (-40~+40)[-20~+20]mm			基準高EL2 (-40~+40)[-20~+20]mm			基準高EL3 (-40~+40)[-20~+20]mm			厚さt1 (-25~)[-13~]mm			厚さt2 (-25~)[-13~]mm			厚さt3 (-25~)[-13~]mm		
		設計 m	実測 m	誤差 m	設計 m	実測 m	誤差 m	設計 m	実測 m	誤差 m	設計 mm	実測 mm	誤差 mm	設計 mm	実測 mm	誤差 mm	設計 mm	実測 mm	誤差 mm
	No.0																		
H22.8.1		100.000	99.990	-0.010	100.000	99.990	-0.010	100.000	99.990	-0.010	20	21	1	20	21	1	20	21	1
	No.1																		
H22.8.2		110.000	110.020	0.020	110.000	110.020	0.020	110.000	110.020	0.020	20	22	2	20	22	2	20	22	2
	No.2																		
H22.8.2		120.000	120.035	0.035	120.000	120.035	0.035	120.000	120.035	0.035	20	24	4	20	24	4	20	24	4
	No.3																		
H22.8.3		130.000	129.965	-0.035	130.000	129.965	-0.035	130.000	129.965	-0.035	20	32	12	20	32	12	20	32	12
	No.4																		
H22.8.3		140.000	139.985	-0.015	140.000	139.985	-0.015	140.000	139.985	-0.015	20	23	3	20	23	3	20	23	3
	No.5																		
H22.8.4		150.000	150.020	0.020	150.000	150.020	0.020	150.000	150.020	0.020	20	18	-2	20	18	-2	20	18	-2
	No.6																		
H22.8.4		160.000	160.025	0.025	160.000	160.025	0.025	160.000	160.025	0.025	20	27	7	20	27	7	20	27	7

3段書 上段 検査職員測定値
 中段 監督職員測定値
 下段 管理値
 測定位置のわかる略図を必要に応じ記入のこと。

